

# New look from October 2020



Order Code  
**JPL-501S-USB**

Order Code  
**JPL-502S-USB**

## TECHNICAL DATA

### Microphone:

Directional: Bi-directional  
 Impedance: Max. 2.2K $\Omega$  (RL=2.2K $\Omega$ )  
 Sensitivity: -43 $\pm$ 3dB RL=2.2K $\Omega$  Vs=2.0V (DC)  
 Frequency Range: 100-10000Hz  
 Operating Temp: -25 $^{\circ}$ C~+70 $^{\circ}$ C  
 Storage Temp: -40 $^{\circ}$ C~+80 $^{\circ}$ C

### Speaker:

Impedance: 24 $\Omega$   $\pm$ 15% at 0.1 V1000Hz  
 Sound pressure: 132dB  $\pm$  3dB at 1000HZ  
 Frequency range: FO ~20KHZ( $\pm$ 10dB)  
 FO: 150Hz  $\pm$  20%  
 Operating Temp: -25 $^{\circ}$ C 50 $^{\circ}$ C  
 Storage Temp: -25 $^{\circ}$ C 60 $^{\circ}$ C



USB-A



CLOTHING CLIP



## JPL-501S-USB / JPL-502S-USB

Universal 'Plug & Play' USB office and contact centre headset. No software download needed. Works with any softphone. New look with padded headband cushion and dark blue details.

### Overview

Features	Single or dual speaker options Fitted with headband cushion for maximum all day comfort Fitted with 55mm leatherette ear cushions Surround Shield™ noise cancelling microphone Clear, crisp sound In-line control with volume & mute Left / right side microphone placement 'Put and stay' ratchet microphone boom arm Overhead, sure-fit fully adjustable headband
What's included	Clothing clip, Quick Start Guide
Headset Weight	Mid-weight Headset, ~ 76g / ~110g
Connection	USB-A
Compatibility	Direct Plug-in
Certifications	CE, RoHS, REACH
Warranty	2 Years repair or replacement warranty
MOQ	Master Shipping Carton: 80
EAN:	JPL-501S-USB: 5060126958055, JPL-502S-USB: 5060126958079
SKU:	JPL-501S-USB: 575-329-001, JPL-502S-USB: 575-329-002

